



# COB62A PENDANT STATION



CE  
ISO9001



Water Proof



2A/  
500VAC  
Contacts load  
capacity



## TECHNICAL DETAILS

Number of buttons	6
Contacts load capacity at resistive load	2A/500VAC
Number of positions	2 [pos.]
Number of stable positions	1 [pos.]
Dimensions	257x68x50 [mm]
Contacts configuration	SPST
Housing material	PVC
Model	COB-62A
Key marker	ON/OFF/UP/DOWN/EAST/WEST
Button shape	convex round
Buttons color	white/red/green



## Characteristics

- **DURABLE ABS SHELL:** Crane controller adopt ABS shell, corrosion resistant, aging resistant, beautiful and durable
- **DUSTPROOF AND RAINPROOF RUBBER JOINT SLEEVE:** Equipped with a rubber joint sleeve, dustproof and rainproof, which guarantees a stable connection
- **REMOTE CONTROL VARIOUS EQUIPMENT:** Control station is suitable for remote control of cranes, car tailgates, electric hoists and other equipment
- **220V/500V WORKING VOLTAGE:** Contact rated working voltage is 220V/500V, contact rated working current for 5A, possess stable performance
- **IP65 PROTECTION LEVEL:** The electrical life is 500,000 times, the mechanical life is 1 million times, and the protection level is IP65