



# LIMIT SWITCH

## SE-8107-A



CE  
ISO9001



Mechanical Life



Degree  
of protection



### TECHNICAL DETAILS

Body	Metal Body
Operation speed	0.5mm - 50cm/sec
Operation speed	Mechanical : 120 operations/ minute Electrical: 30 operations/minute
Contact Resistance	25m $\Omega$ max. (initial value)
Insulation Resistance	100m $\Omega$ min(below 500VDC)
Dielectric Strength	1000VAC, 50/60Hz for 1 minute between terminals of the same polarity 1500VAC, 50/60 Hz for 1 minute between current-carrying and non-current-carrying metal parts 50/60 Hz for 1 minute between each terminal and ground
Vibration	10 55Hz, 1.5mm 10-55Hz 1.5mm double amplitude Mechanical durbie 1,000m/Sec
Shock	Malfunction: 300m/Sec
Ambient Temperature	- 5 ~ + 65 C
Humidity	95% RH
Life	Mechanical 10,000,000 operations above Electrical 500,000 operations above
Weight	130 to 190g
Degree of Protection	IP 65

- **This Limit switch features a compact design and a long mechanical life.**
- **They have easy wiring with full open terminals and dust, water, oil proof construction.**
- **It is operated by the motion of a machine part or presence of an object.**
- **The defining feature of it is that a relatively small movement at the actuator button produces a relatively large movement at the electrical contacts, which occurs at high speed (regardless of the speed of actuation).**