



# SIBASS SOILNED COIL



CE  
ISO9001

CODE	RATED VOLTAGE (V)	RATED FORCE (N)	RATED STROKE (mm)	OPERATING FREQUENCY (T/h)	WEIGHT (kg)
SE-1502	36 110 220 380	5	10	1500	0.5
SE-1602	36 110 220 380	10	15	1200	1
SE-2502	36 110 220 380	15	15	1200	1.5
SE-2602	36 110 220 380	20	15	1200	2
SE-3502	36 110 220 380	30	20	750	3
SE-3602	36 110 220 380	40	20	750	4



## DESCRIPTION

**This series solenoid is applied to AC 50Hz, which voltage can reach 380V, it can be used as a power components of machine equipment and the automatic system to realise the thle-control of the various outfits and the mechanical trig. Of which performance is the same as that of SA products.**

- **Install at the place where there is no marketed shack of motion.**
- **There is no gas dust which can corrupt or destory non conductor. Or,it will affected thr products lifetime.**
- **The solenoids fit for the character of services as follow disconnected continuous duty system, intermittent recycled duty system.**
- **The reasonable wave gauge of supply voltage is between 85% -110% (any special requirements is possible ).**

**When the solenoids have used for a long time, they may produce noise and cannot be stroked, you can disassemble the solenoids, cleaning the oil stain and the dirtiness form thr pole of armature in order to avoid the coil from burning.**