



# SIBASS THERMAL OVER LOAD RELAY



CE  
ISO9001

TYPE	RATED WORKING CURRENT OF THERMAL RELAY	REGULAR OR SCALE OF RATED CURRENT		
		RATED CURRENT (A)	TERMINAL COMPONENT	
SE-LR2-D13	25	SE-LR2-D1301	0.16	0.10-1.16
		SE-LR2-D1302	0.25	0.16-0.25
		SE-LR2-D1303	0.40	0.25-0.40
		SE-LR2-D1304	0.63	0.40-0.63
		SE-LR2-D1305	1.0	0.63-1.0
		SE-LR2-D1306	1.6	1.0-1.6
		SE-LR2-D13X6	2.0	1.6-2.0
		SE-LR2-D1307	2.5	2.0-2.5
		SE-LR2-D1308	4.0	2.5-4.0
		SE-LR2-D1310	6.0	4.0-6.0
		SE-LR2-D1312	8.0	5.5-8.0
		SE-LR2-D1314	10.0	7.0-10.0
		SE-LR2-D1316	13.0	9.0-13.0
		SE-LR2-D1321	18.0	12.0-18.0
SE-LR2-D23	36	SE-LR2-D1322	25.0	17.0-25.0
		SE-LR2-D1352	32	23.0-32.0
		SE-LR2-D1355	36.0	28.0-36.0



## Description

**This series of thermal relay can be used in the circuit of 50Hz or 60Hz, rated insulation voltage 660V, rated current 0.1-93A for protecting the phase break when the electric motor is overload. The relay has different mechanism and temperature compensation & can be plugged in SE-LC1-D series AC contactor.**